



## Height Restriction

### ES5600 Height Restriction Barrier



### ES5600

The ES5600 Height Restrictor Barrier is constructed from high quality steel rectangular box section.

It provides an ideal solution for the prevention of access for high vehicles to unauthorised areas such as staff car parks or underground low level car parks. It is a durable and reliable restriction barrier, available as single or double leaf, either standard or heavy duty box section.

Clear signage allows vehicle occupants the opportunity to determine whether they have sufficient clearance to proceed under the cross beam in order to access. The opening variants can be locked in either open or closed position via an additional latch post and a padlock respectively.

<b>Specification</b>	Steel Constructed Height Restriction Barrier
<b>Material</b>	Mild Steel Squared Hollow Section
<b>Construction - Standard</b>	Gates - 60 x 60 x 3mm / Posts 100 x 100 x 100mm
<b>Construction - Heavy Duty</b>	Gates - 80 x 80 x 5mm / Posts 150 x 150 x 5mm
<b>Finish</b>	Powder Coated as Standard & Galvanised (Additional Cost)
<b>Fittings</b>	Comes Complete with Padlock & Fixings
<b>Available Span</b>	From 2.0 - 6.0 Metres (Single Leaf) 12 Metres (Double Leaf)
<b>Installation</b>	Posts may be either Sunken or Surface Mounted